SchizConnect:

Large-Scale Schizophrenia Neuroimaging Data Integration and Sharing

Lei Wang, Jose Luis Ambite, Jessica Turner, Steven Potkin

September 16, 2014 NIMH

Outline

- I. Introduction
- II. SchizConnect
- III. Demonstration
- IV. Next steps

I. Introduction

- Where is schizophrenia neuroimaging data?
- Data sharing challenges
- SchizConnect solution
- Datasets in SchizConnect
- Data compatibility

Where is schizophrenia neuroimaging data?

- Institutional databases:
 - COINS (MCIC, COBRE), XNAT Central (NUSDAST)
- Federated databases:
 - FBIRN
- Individual labs
 - ENGIMA Schizoprhenia Working Group
 - Numerous "unincorporated" others

ENGIMA Schizoprhenia Working Group

Sample	N (Total)	M/F	M/F	Mean Age	Mean Age	Mean Age	Mean DOI	PANSS	SANS	SAPS	mean
		(HC)	(SZ)	(HC)	(SZ)	of Onset		Total	Total	Total	CPZ
AMC*	376	114/56	180/26	23.3	22.1	20	2	69			276
CLING*	372	132/191	36/13	25.2	32.4	21	11	51			638
Dublin*	284	98/129	39/18	29.9	42.6	23	20				344
Edin-	36	10/10	9/7	37.6	36.3	23	16	43			433
burgh											
FBIRN**	365	127/51	141/46	37.5	38.9	22	17	69	22	16	510
Galway	154	46/28	56/24	34.2	33.3	24	10	36	15	8	704
HMS	101	21/34	32/14	39.6	28.4	28	8.0	90			313
HUBIN	200	73/31	70/26	41.6	42	25	17		32	14	
MCIC**	323	103/62	119/39	31.4	33.5	23	11		21	18	553
NU	201	52/41	74/34	32	34.2	21	13		33	23	
Olin*	888	259/300	184/145	37.9	37.4	25	13	66			
PAFIP	229	51/30	91/57	27.6	29.6	29	2		18	41	
TOP	524	160/145	130/89	35.4	32	26	7	62			449
UMCU	275	72/44	130/29	32.9	31	21	11	60			394
UPENN*	370	89/104	105/72	35.9	38.4	21	17		24	18	343
Total	4698	1407/1256	1401/634	31.1	33.8	23	11	64	23	21	436

van Erp, T.G.M., Hibar, D.P., Rasmussen, J., Andreassen, O.A., Haukvik, U.K., Agartz, I., Potkin, S.G., Hulshoff-Pol, H., Ophoff, R., Haren, N.E.M.v., Gruber, O., Krämer, B., Erhlich, S., Hass, J., Wang, L., Alpert, K., Pearlson, G.D., Glahn, D., Thompson, P.M., Turner, J.A., 2014. Subcortical and cortical variations in schizophrenia: the ENIGMA SZ Working Group. Human Brain Mapping, Hamburg, Germany.

Data sharing challenges

- User interacts directly with individual sites
- Different data use agreements
- Needs to understand and relate data organization, variables and values from all sites
- Data transfer
- Example: COINS + FBIRN + NU
 - Turner, J.A., et al, 2012. Heritability of multivariate gray matter measures in schizophrenia. Twin Res Hum Genet 15, 324-335.

SchizConnect solution

- User interacts with one portal
- Data modeling with common ontology
- Facilitate user authentication, compliance with data use agreements & data transfer
- Test bed of 3 data sources: MCIC/COBRE (COINS), FBIRN, NUSDAST (XNAT Central), expand to including others

Datasets

	NU	FBIRN	MRN			
Database	XNAT	HID	COINS			
# Subjects	Cu	ırrently availab	le			
	570 (451 with 1.5T)	237 (Phase II)	432 (213 MCIC 219 COBRE)			
	To be released					
New subjects	130 (3T)	400 (Phase 3)	200 (R01)			
Timeline	Y2	Y3	Y3-Y4			

Data types: More complex than the number of individual subjects

	NU	FBIRN	MRN	
Database	XNAT	HID COINS		
		Additional types		
		Resting fMRI	Resting fMRI	
	-	Task fMRI	Task fMRI	
		DTI	DTI	
		To be released		
	Structural MRI	Structural MRI	Structural MRI	
Now subjects	Resting fMRI	Resting fMRI	Resting fMRI	
New subjects	Task fMRI	Task fMRI	Task fMRI	
	DTI	DTI	DTI	
Timeline	Y2	Y3	Y3-Y4	



Imaging Data Compatibility

- Compatible definitions at all 3 data sources
- SchizConnect Ontology
- Mapping to NeuroLEX, INCF standards
 - Facilitating common terms where possible across SchizConnect and other projects
 - Number of terms linked:15 (out of 19 modeled)

SchizConnect	INCF/NeuroLEX
Imaging_Protocol	Image
Structural	None
T1	T1-weighted 3D image
T2	T2-weighted 3D image
Difusion	Diffusion-weighted 3D image
Perfusion	Perfusion-weighted 3D image
Functional	None
Resting_State	TBD
Task_Paradigm	birnlex_2075/COGPO_0049
Auditory_Oddball	birnlex_2161
Breath_Hold	birnlex_2007
Mismatch_Negativity	birnlex_2181
Sternberg_Item_Reco	birnlex_2031
Finger_Tapping	nlx_145967/CAO_00745
Sensory_Motor	nlx_146049/CAO_00827
Go_NoGo	birnlex_2047 (finger tapping's defini
Working_Memory	TBD
Field_Mapping	TBD




Meta Data Compatibility


- Compatible definitions at all 3 data sources
- SchizConnect Ontology
- Mapping to NeuroLEX, INCF standards
 - Facilitating common terms where possible across SchizConnect and other projects
 - Number of terms linked:TBD


SchizConnect Common Terms
Diagnosis
Mental_Disorder
Psychotic_Disorder
Schizophrenia_Broad
Schizophrenia_Strict
Schizoaffective
Bipolar_Disorder
Physical_Disorder
Neurological_Disorder
Possible_Disorder
Sibling_of_Schizophrenia_Strict
No_Known_Disorder
Sibling_of_No_Known_Disorder

II. SchizConnect









A Sample Query Query Results

Your query returned 1,046 downloadable images from 250 subjects. View My Qu

- COBRE (COINS): 129 downloadable images from 47 distinct subjects
- MCICShare (COINS): 144 downloadable images from 54 distinct subjects
- fBIRNPhaseII_0010 (HID): 308 downloadable images from 60 distinct subjects
- NUDataSharing (NUSDAST): 465 downloadable images from 89 distinct subjects

Note that some subjects have longidinal data, some visits contain multiple imaging sequences, and some scans have multiple formats.

To review your query, please use the View My Query link (the back button will take you to a blank query creation page).

Click the "Proceed to Image Download" button below to sign Data Use Agreements and begin package creation. Your package will inc the table below.

Please note that you will need 7zip to extract the contents of the downloaded package.

Proceed to Image Download

10 \$ records per page

Se

ima

sig

ead

Provenance	Name \$	Subjectid	Age	Sex	Dx ≎	Field_strength	Datauri	Maker
COME		A00000808		main	Schizophrenia, Strict			Secure
COMB		A20000808		main	Schizophrania, Strict			1.6

A Sample Ouery Image Download

- One-click Interface
- Without having to register, the user can obtain a total count on the number of available datasets
- SchizConnect will facilitate user registration and compliance with data use agreement with each site
- User can download specific datasets without having to go to each data site
- The user can download both queried data and un-queried data associated with subjects satisfying the query criteria

MCIC Data Usage Agreement



SchizConnect Mediator

- Mediator is developed and deployed at USC/ISI
- Defines a virtual common schema for all sources
- Maps between source schemas and common schema
- Accepts user/client SQL queries over common schema
- Translates user query from common schema to source schemas
- Queries each data source in parallel (currently 3)
 - HID@UCI, NUSDAST@XNATCentral, COINS@MRN
- Mediator accepts SQL queries from:
 - SchizConnect web portal
 - Application programs can send queries to Mediator (with credentials)

SchizConnect Mediator Source Schemas

```
HIDPSQLResource nc experiment(uniqueid:NUMBER:f, tableid:NUMBER:f, owner:NUMBER:f,
  modtime:DATE:f, moduser:NUMBER:f, name:STRING:f, description:STRING:f, contactperson:STRING:f, ....)
HIDPSQLResource nc subjexperiment(uniqueid:NUMBER:f, ... subjectid:STRING:f, ....)
HIDPSQLResource nc expsegment( segmentid, componentid, ..., subjectid, ...
 time stamp:DATE:f, description:STRING:f, protocolversion, protocolid:STRING:f, ...)
HIDPSQLResource nc collectionequipment(uniqueid, tableid, owner, modtime:DATE:f, ..., make, model)
XnatSubjectResource xnat subjectData(PROJECT, SUBJECT ID)
XnatMRSessionResource xnat mrSessionData( PROJECT, SCANNER, MARKER)
COINSMySQLResource subjects v(ANONYMIZATION_ID, GENDER, YOB, SUBJECT_TYPE, STUDY_ID, AGE)
COINSMySQLResource series v(Series_ID, AnonyMization_ID, AGE_AT_SCAN, SCAN_DATE_YEAR,
SCAN DATE, COLLECTION TECHNIQUE, DEFINITION, SCANNER LABEL, SCANNER MODEL, ...)
MappingsMySQLResource protocol mappings(szc_protocol_hier, source, protocolid)
MappingsMySQLResource scanner mappings(maker, model, field_strength, source, source_make,
source model)
                                                                                            19
```


SchizConnect Mediator (Virtual) Common Schema

project(provenance:STRING, name:STRING, projectid:NUMBER, description:STRING)

subject(provenance, subjectid, age, sex, dx)

in_project(provenance, subjectid, projectid)

imaging_protocol(provenance, subjected, szc_protocol_hier, img_date:DATE,
 notes, datauri, maker, model, field_strength)



SchizConnect Mediator Schema Mappings (1)

```
imaging protocol("HID", SUBJECTID, SZC_PROTOCOL_HIER, DATE, NOTES, DATAURI,
                    MAKER, MODEL, FIELD STRENGTH) <-
 HIDPSQLResource nc scannersbyscan mview(SUBJECTID, componentid, segmentid,
      SOURCE PROTOCOL, DATE, nc coleguipment uniqueid, SOURCE MAKE, SOURCE MODEL,
      DATAURI, NOTES) ^
 MappingsMySQLResource_protocol_mappings(SZC_PROTOCOL_HIER, "HID",
                                          SOURCE PROTOCOL, ID1) ^
 MappingsMySQLResource scanner mappings (MAKER, MODEL, FIELD STRENGTH, "HID",
                                           SOURCE MAKE, SOURCE MODEL, ID2)
imaging protocol ("NUSDAST", SUBJECTID, SZC PROTOCOL HIER, DATE, SCAN ID, DATA URI,
                   "SIEMENS", "VISION 1.5T", 1.5) <-
  XnatMRSessionResource_xnat__mrSessionData( SUBJECTID, IMAGE_ID, SESSION_ID, DATE,
                                      SCANNER, SCAN_ID, SCAN_TYPE, quarantine status) ^
  MappingsMySQLResource_protocol_mappings(SZC_PROTOCOL_HIER, "NUSDAST", SCAN_TYPE, ID1) ^
  Concat(IMAGE ID, "/scans/", SCAN ID, DATA URI)
```

• • •

SchizConnect Mediator Schema Mappings (2)

Algorithm for DX from HID assessment data:

```
subject dx("HID",SUBJECTID, 'No Known Disorder') <-</pre>
```

HIDPSQLResource_nc_subjexperiment(uniqueid, tableid, owner, modtime, moduser, nc_exp_uniqueid, SUBJECTID, nc_researchgroup_uniqueid) ^ (nc_researchgroup_uniqueid IN [9612,4292]) ^ (nc_experiment_uniqueid = 9610)

subject_dx("HID",SUBJECTID, 'Mental_Disorder>Psychotic_Disorder>Schizophrenia_Broad>Schizophrenia_Strict') <-</pre>

HIDPSQLResource_nc_subjexperiment(uniqueid, tableid, owner, modtime, moduser, nc_exp_uniqueid, SUBJECTID, nc_researchgroup_uniqueid) ^ (nc_researchgroup_uniqueid = 9611) ^ (nc_experiment_uniqueid = 9610) ^

HIDPSQLResource_nc_assessmentinteger(tableid1, nc_assessmentdata_uniqueid1, scoreorder1, owner1, modtime1, moduser1, textvalue1, textnormvalue1, comments1, DATAVALUE1, datanormvalue1, storedassessmentid1, ASSESSMENTID1, SCORENAME1, scoretype1, ISVALIDATED1, isranked1, SUBJECTID, entryid1, keyerid1, raterid1, classification1, uniqueid1) ^

(ASSESSMENTID1 = 16415) ^ (SCORENAME1 = "SCID_P47") ^ (DATAVALUE1 = 3) ^ (ISVALIDATED1 = "TRUE") ^

HIDPSQLResource_nc_assessmentinteger(tableid2, nc_assessmentdata_uniqueid2, scoreorder2, owner2, modtime2, moduser2, textvalue2, textnormvalue2, comments2, DATAVALUE2, datanormvalue2, storedassessmentid2, ASSESSMENTID2, SCORENAME2, scoretype2, ISVALIDATED2, isranked2, SUBJECTID, entryid2, keyerid2, raterid2, classification2, uniqueid2) ^

(ASSESSMENTID2 = 16415) ^ (SCORENAME2 = "SCID P53") ^ (DATAVALUE2 = 1) ^ (ISVALIDATED2 = "TRUE")

subject_dx("HID",SUBJECTID, 'Mental_Disorder>Psychotic_Disorder>Schizophrenia_Broad>Schizoaffective') <-</pre>

HIDPSQLResource_nc_subjexperiment(uniqueid, tableid, owner, modtime, moduser, nc_exp_uniqueid, SUBJECTID, nc_researchgroup_uniqueid) ^ (nc_researchgroup_uniqueid = 9611) ^ (nc_experiment_uniqueid = 9610) ^

HIDPSQLResource_nc_assessmentinteger(tableid1, nc_assessmentdata_uniqueid1, scoreorder1, owner1, modtime1, moduser1, textvalue1, textnormvalue1, comments1, DATAVALUE1, datanormvalue1, storedassessmentid1, ASSESSMENTID1, SCORENAME1, scoretype1, ISVALIDATED1, isranked1, SUBJECTID, entryid1, keyerid1, raterid1, classification1, uniqueid1) ^

(ASSESSMENTID1 = 16415) ^ (SCORENAME1 = "SCID_P53") ^ (DATAVALUE1 = 3) ^ (ISVALIDATED1 = "TRUE")

SchizConnect Mediator Query Rewriting

Using the schema mappings the SchizConnect mediator rewrites queries over the domain schema to queries over the source schemas

- Domain Query (over domain schema):
 SELECT * FROM imaging protocol WHERE szc protocol hier like '%Auditory Oddball%'
- Rewritten Query (over source schemas):

```
(SELECT 'HID' as provenance, T6.subjectid as subjectid, T4.szc_protocol_hier as szc_protocol_hier, T6.date as img_date,
T6.description as notes, T6.datauri as datauri, T2.maker as maker, T2.model as model, T2.field_strength as field_strength
FROM MappingsMySQLResource_scanner_mappings T2, MappingsMySQLResource_protocol_mappings T4,
HIDPSQLResource_nc_scannersbyscan_mview T6
```

WHERE T2.source_make=T6.source_make and T2.source_model=T6.source_model and T2.source = 'HID' and T4.source_protocol=T6.source_protocol and T4.source = 'HID' and T4.szc_protocol_hier LIKE '%Auditory Oddball%')
UNION


(SELECT 'NUSDAST' as provenance, T10.SUBJECT_ID as subjected, T8.szc_protocol_hier as szc_protocol_hier, T10.SCAN_DATE as img_date, T10.SCAN_ID as notes, Concat(T10.IMAGE_ID,'/scans/',T10.SCAN_ID) as datauri, 'SIEMENS' as maker, 'VISION 1.5T' as model, 1.5 as field_strength

FROM MappingsMySQLResource_protocol_mappings T8, XnatMRSessionResource_xnat__mrSessionData T10
WHERE T8.source_protocol=T10.SCAN_TYPE and T8.source = 'NUSDAST' and T8.szc_protocol_hier LIKE '%Auditory Oddball%')
UNION

(SELECT 'COINS' as provenance, T12.ANONYMIZATION_ID as subjected, T12.szc_protocol_hier as szc_protocol_hier, T12.SCAN_DATE as img_date, 'notes' as notes, T12.SERIES_ID as datauri, T12.SCANNER_MANUFACTURER as maker, T12.SCANNER_LABEL as model, T12.FIELD_STRENGTH as field_strength


FROM COINSMySQLResource_series_v T12

SchizConnect Architecture & Data Flow






Query: Web Portal -> Mediator






Query: Mediator \rightarrow Data sources In Parallel





Query: Mediator \rightarrow Data sources HID



HID Data Source

FBIRN – Federated data http://fbirnbdr.nbirn.net:808 0/BDR

XNAT Data Source

data archival system

http://niacal.northwestern.edu/xnat gueries/NUSDAST


COINS Data Source

MCIC & COBRE – Federated, subsets

http://coins.mrn.org




Query: Mediator \rightarrow Data sources XNAT





Query: Mediator \rightarrow Data sources COINS



HID Data Source

FBIRN — Federated data http://fbirnbdr.nbirn.net:808 0/BDR

XNAT Data Source

NUSDAST – Project within a data archival system

http://niacal.northwestern.edu/xnat queries/NUSDAST


COINS Data Source

MCIC & COBRE – Federated, subsets

Special Handling: View at USC http://coins.mrn.org




Query: Mediator \rightarrow Data sources Join






Query return: Mediator -> Web Portal





Data download: DUA



- SchizConnect DUA is at the top of all DUAs always mandatory
- Individual Data Source DUA optional
 - One time for data source admin
 - Admin creates DUA form on SchizConnect once only
 - DUA displayed on SchizConnect.org web portal
 - May need user-input info (such as institution, purpose etc)
- User to check boxes for agreeing once only
- DUA pdf is viewable
- DUA pdf is emailed to user & data source admin
- Data download button activated


Data download: DUA







Data download: DUA





Data download: HID

SchizConnect.org **Data Warehouse** Web Portal **Mediator Interface Data Source Interface**

- SchizConnect.org interact with HID directly, without going through the Mediator
- Ensure that HID DUA is signed
- Download scans with HID gridFTP script (in background) on SchizConnect server
- Create a 7z archive of all HID scans (broken into 10GB "chunks" for quick download)

HID Data Source

FBIRN - Federated data http://fbirnbdr.nbirn.net:808 0/BDR

COINS Data Source

MCIC & COBRE – Federated.

Data

gridFTP



Data download: XNAT

SchizConnect.org Web Portal Mediator Interface Data Warehouse Data Source Interface

- SchizConnect.org interact with XNAT directly, without going through the Mediator
- Ensure that XNAT DUA is signed
- Download scans with XNAT REST API (in background) on SchizConnect server
- Create a 7z archive of all XNAT scans (broken into 10GB "chunks" for quick download)

HID Data Source

FBIRN — Federated data <u>http://fbirnbdr.nbirn.net:808</u> 0/BDR

XNAT Data Source

NUSDAST – Project within a data archival system

http://niacal.northwestern.edu/xnat queries/NUSDAST

COINS Data Source

Data

API

MCIC & COBRE - Federated,

subsets

http://coins.mrn.org



Data download: COINS

SchizConnect.org Web Portal Mediator Interface Data Warehouse Data Source Interface

- SchizConnect.org interact with COINS directly, without going through the Mediator
- Ensure that COINS DUA is signed
- Download scans with HTTP (in background) on SchizConnect server
- Create a 7z archive of all COINS scans (broken into 10GB "chunks" for quick download)

HID Data Source

FBIRN — Federated data <u>http://fbirnbdr.nbirn.net:808</u> 0/BDR

XNAT Data Source

NUSDAST – Project within a data archival system

http://niacal.northwestern.edu/xnat gueries/NUSDAST

COINS Data Source

Data

HTTP

MCIC & COBRE – Federated, subsets

http://coins.mrn.org



Data download: Email

Wait for all scans to finish downloading from all data sources (they may take

Dear Lei Wang,

The images you requested in query 40 + T1 are available for download on SchizConnect.

Please click each link below to download the data. These links will expire on September 29, 2014 at 10:22am Central Time.

- COINS Images (1 of 1): <u>schizconnect COINS images 20140915094447 3.7z.001</u> (395 MB)
- HID Images (1 of 1): <u>schizconnect HID images 20140915094447 3.7z.001</u> (158 MB)
- NUSDAST Images (1 of 1): <u>schizconnect NUSDAST images 20140915094447 3.7z.001</u> (333 MB)
- Meta-Data: schizconnect metaData 20140915094447 3.csv (17.4 KB)
- Once you have downloaded all 7z files, you can extract the archives by running the commands below or with the 7zip GUI.
 - 7z x schizconnect_COINS_images_20140915094447_3.7z.001
 - 7z x schizconnect HID images 20140915094447 3.7z.001
 - 7z x schizconnect_NUSDAST_images_20140915094447_3.7z.001

Please note: if you have multiple 7z files from a given data source (i.e., extensions like *7z.001, *7z.002, etc.), they are all part of a single archive. You only need to run the extraction on the *.7z.001 files to extract all the images in your package.

If you do not have the 7zip utility, you can download it from the 7zip website.


Please reply to this email with any issues.

Regards,


The SchizConnect Team


III. Demonstration


- Drag-n-drop query GUI
- Two-phase return
 - Summary counts without signing in
 - Subject-level data after signing in
- DUA
- Download
- Example queries for schizophrenia research



SchizConnect About Data leiwang1@northwestern.ed 40 + T1 Query Results Your query returned 97 downloadable images from 20 subjects. View My Query or Create New Query COBRE (COINS): 12 downloadable images from 4 distinct subjects MCICShare (COINS): 12 downloadable images from 4 distinct subjects • fBIRNPhaseII__0010 (HID): 40 downloadable images from 6 distinct subjects • NUDataSharing (NUSDAST): 33 downloadable images from 6 distinct subjects Note that some subjects have longidinal data, some visits contain multiple imaging sequences, and some scans have multiple formats. To review your query, please use the View My Query link (the back button will take you to a blank query creation page). To download these images and/or view summary data, please Sign In. © 2014 SchizConnect








- Hierarchical search
 - Sternberg & SCZ-broad: return = 1,462
 - Sternberg & SCZ-broad & 3T: return = 841
 - Sternberg & SCZ-strict & 3T: return = 489
 - Sternberg & SCZ-strict & 3T & age <=30: return = 210



© 2014 SchizConnect



17:59:12.0

- 40 + T1
- Male <= 40 yr 1.5T T1
- Sternberg SCZ-strict 3T <=30
- RESTing BP+CON
- T1 (SCZ+CON) 20-50 3T
- SCZ+CON 1.5T T1
- ALL Images

IV. Next Steps

- Dissemination
- Enhanced interface for more complex queries
- Additional variables
- Additional data types
- Additional datasets/subjects
- Additional data sources

Dissemination

- Paper
- Presentations
 - OHBM 2013 ("Sources of actual imaging data for mega- or meta-analyses," J Turner)
 - ACNP 2014 (Submitted)
 - ICOSR 2015 (To be submitted)
- Big Data Tool R01
 - 1R01EB020062-01, Neurodegenerative and Neurodevelopmental Subcortical Shape Diffeomorphometry (Miller, M, PI)

Additional Variables

- Symptom domains
 - PANS
 - SAPS/SANS
- Neuropsychological domains
 - WM (Working Memory)
 - EM (Episodic Memory)
 - EF (Executive Function)

Additional Data Types

	NU	FBIRN	MRN
Database	XNAT	HID	COINS
	Additional types		
		Resting fMRI	Resting fMRI
	-	Task fMRI	Task fMRI
		DTI	DTI
		To be released	
New subjects	Structural MRI	Structural MRI	Structural MRI
	Resting fMRI	Resting fMRI	Resting fMRI
	Task fMRI	Task fMRI	Task fMRI
	DTI	DTI	DTI
Timeline	Y2	Y3	Y3-Y4

Additional Datasets

NU	FBIRN	MRN
XNAT	HID	COINS
Currently available		
570	237	432
(451 with 1.5T)	(Phase II)	(213 MCIC
		219 COBRE)
To be released		
130	400	200
(3T)	(Phase 3)	(RO1)
Y2	Y3	Y3-Y4
	XNAT Cu 570 (451 with 1.5T) 130 (3T)	Currently available 570 237 (451 with 1.5T) (Phase II) To be released 130 400 (3T) (Phase 3)


Additional Data Sources


- Up to 3 sites
- At least one site with a substantially different database architecture than XNAT, COINS, HID
- Willingness to participate
- Sample size
- Completeness and quality of data
- Commitment to keeping their database publicly available on an ongoing basis to the research community

Additional Data Sources

• 6 sites expressed interest:

1	Konasale Prasad at UMPC	prasadkm@upmc.edu
2	Carol Tamminga at UTSW	Carol.Tamminga@utsouthwestern.edu
3	Ty Cannon at UCLA, now Yale	cannon@psych.ucla.edu
4	Herb Meltzer at Vanderbilt, now NU	herbert.meltzer@Vanderbilt.Edu
5	Deanna Barch at WUSM	dbarch@artsci.wustl.edu
6	Lynn E. DeLisi at Harvard	DeLisi76@AOL.com





Acknowledgements

- NIMH 1U01 MH097435
- NIMH Collaborators: Drs. Freund, Farber, Rumsey
- SchizConnect Team:
 - Mediator @ USC: Jose Luis Ambite, Marcelo Tallis
 - HID/FBIRN @ UCI: David Keator, Steven G. Potkin
 - COINS/MCIC+COBRE @ MRN: Vince Calhoun,
 Margaret King, Drew Landis, @ GSU: Jessica A. Turner
 - XNAT Central/NUSDAST @ NU: Kathryn I. Alpert, Alex Kogan